





CAPABILITY STATEMENT

KNS LLC is a certified Woman-Owned Small Business located in Dallas, Texas. We are the distributor of Aquaphalt, a cutting-edge, eco-friendly answer to asphalt and concrete repairs. Aquaphalt is a permanent cold patch repair product made of crushed granite and a proprietary plant-based binder with no petroleum or VOCs. Aquaphalt can be applied in freezing and searing hot temperatures, rain, sun, ice and snow. The repair takes three easy steps and can be driven on immediately. Rated #1 by Consumer Reports, endorsed by the National Center for Asphalt Technology, evaluated by the US Army Corps of Engineers, used by DOTs, municipalities, government agencies and contractors all over the country.

CORE COMPETENCIES

- Product made to order
- Production and delivery in less than one week
- Only asphalt repair product with Unlimited Curing Guarantee
- Three-year product warranty best in the industry
- Rated #1 by Consumer Reports
- National Center for Asphalt Technology endorsement
- All-weather, year-round application
- Eco-friendly, NO VOCs
- Territory US and Canada

PAST PERFORMANCE

Fort Sam Houston National Cemetery

Dallas ISD

Fort Worth ISD

Dallas Love Field

Robins Air Force Base

Mississippi DOT

City of Coppell

DFW Airport

Fireman's Paving Contractors

Ferrovial

Tarrant County College District

Texas Tech University

Greater Orlando Airport Authority

COMPANY SNAPSHOT

CAGE CODE: 8AWQ9

DUNS NUMBER: 011298022 TX CMBL VID#1710906716900 SAMS UID#C12DA9VGJ9E5

Government Business POC: Kelly Waterman

Email: Kelly@aquaphalt-kns.com

Phone: 214-923-5476

Address: 4033 Amherst Ave., Dallas, TX 75225

Website: www.Aguaphalt-KNS.com

All Credit Cards accepted

SOCIO-ECONOMIC STATUS

Small Business Enterprise Cert. - Exp. 6/30/25 DBE Cert: Tx, Ohio, Florida - Exp. 2/17/27 (TX)

Woman-Owned Entity Certification - Exp.6/30/25

HUB Texas Certification - Exp. 6/12/27

WBENC - Exp. 5/14/25 WOSB - Exp. 5/14/25







NAICS CODES

237310 — Highway, Street and Bridge Construction

423320 — Brick, Stone and Related Construction
Material Merchant Wholesalers

424120 — Wholesale Trade Agents & Brokers

745-65 — NIGP





- WHAT IS THE COVERAGE RATE OF 1 BUCKET? 5 sq. feet at 1" thick.
- HOW MUCH WATER DO I USE? We recommend 1/2 gallon of water per bucket of Aquaphalt, but you cannot add too much. If water already exists in the pothole, that's great. Just clear the hole of any loose debris.
- CAN I INSTALL AQUAPHALT ON TOP OF A FAILING SUB-GRADE? No, you need to remove asphalt and compact your subgrade before installing Aquaphalt.
- WHAT DO I DO WHEN IT'S BELOW FREEZING? Simply add something to your water to keep it from freezing. Mix in RV
 anti-freeze or salt brine in your water and pour that mixture on top of your Aquaphalt patch then tamp. We
 recommend mixing 4 parts water to 1 part eco-friendly antifreeze.
- WHY SHOULD I USE AQUAPHALT WHEN COLD PATCH IS CHEAPER? Cold patch could be free, but if it doesn't work it is costing your more money. Aquaphalt can be installed in any weather condition, any time of year and will give you a permanent patch. All you need is a hand tamper and water.
- HOW MANY BUCKETS TO PALLET? 36
- WHAT IS THE BUCKET SIZE? 3.5 gallon. 50 lbs.
- WHAT IS THE WARRANTY? 3-year warranty if installed at least 1" thick. AND Unlimited Curing Guarantee.
- SHELF LIFE? 12 months. Please store correctly indoors out of the elements.
- CAN I SAVE ANY UNUSED AQUAPHALT LEFT IN THE BUCKET? Yes, just reseal and try to use within 30 days.
- HOW LONG DOES IT TAKE TO CURE? The curing process begins as soon as you apply the water to activate the binder. Depending on the weather, it will be cured within 2-12 hours. It can be driving on immediately.
- CAN I SEAL OR STRIPE IT? Yes, you can. We suggest you wait 24 hours.
- SUGGESTIONS FOR FILLING A DEEP POTHOLE? For deep potholes, apply Aquaphalt in 2" layers. Apply, water, tamp then repeat. This gives you a real solid repair.
- WHAT ARE THE DIFFERENT SIZES? Aquaphalt 4.0 is a finer aggregate ideally for utility cuts and more shallow areas. Aquaphalt 6.0 is the medium aggregate, typically used for standard pothole repair. Aquaphalt 9.0 is a larger aggregate for deeper repairs. Aquaphalt 4.0 costs slightly more due to the milling process.













